

## Newton Systems



## STEAM TRAP SERIES

Inverted Bucket Steam  
Trap SBT10A

# Inverted Bucket Steam Trap

## SBT10A Inverted Bucket Steam Trap




### Technical Parameter

Nominal pressure	PN25
Max. allowable pressure (Shell)	2.45MPa/200°C
Max. allowable temperature (Shell)	450°C/1.03MPa
Factory steam action test	>3 times/1.6MPa
Max. operating pressure	1.6MPa
Max. operating temperature	350°C
Factory cold test pressure	3.8MPa
Air test	2.0MPa

### Material list

Bonnet : A105/F304/F316      Disc: 440C+304  
 Body : WCB/CF8/CF8M      Other internal parts: 304  
 Seat : 420

### SBT10A Capacity Curve



### Working Principle

- Based on the differential density of steam and liquid.


### Features

- The valve body and valve cover are all made of forged steel/cast steel.
- Internal parts are all made of stainless steel and added with anti-wear allowance, extend trap life.
- U-shaped flow channel design, to achieve water sealing effect, no leakage of steam.
- Reliable flexible closure system with patented technology, no steam leakage.
- Install anti-water hammer device.
- Built-in check valve, suitable for superheated steam environment.
- Built-in filter allows the steam trap to work in a clean environment.
- Select different capacity curves according to the pressure difference to increase the capacity
- The back pressure rate is as high as 90% or more.
- After the steam is stopped, the condensed water can be removed by opening the screw plug to prevent damage to the steam trap due to low temperature freezing.

### Technical Standard

- GB/T12250-2005 Steam Trap Terminology Marking Structure Length
- GB/T22654-2008 Technical Conditions for Steam Trap
- GB/T12251-2005 Test Methods for Steam Trap
- ISO 6948 Automatic steam trap  
Production and performance characteristic tests

### Structure Diagram



### Structural Dimension Table

Model	Size	L	H	H1	W	Unit(mm)
						Weight
SBT10AT	DN15-25	130	186	113	100	4Kg
SBT10AW	DN15-25	130	186	113	100	4Kg
SBT10AF	DN15-25	190	186	113	100	6.5Kg



**VMV** Newton Systems®

## **ZHEJIANG NEWTON FLUID CONTROL CO.,LTD.**

### **Headquarters (Wenzhou)**

Zhiyi road, Lingxia industrial zone, Wuniu, Wenzhou,  
Zhejiang, China.

Tel: 86-577-67978269

Fax: 86-577-67376711

E-mail: [vmv@vmv-valve.com](mailto:vmv@vmv-valve.com)

### **Shanghai R&D Center**

Jiading District, Shanghai  
Building 12A, Chengbei Road  
Tel: 86-18057752663

E-mail: [vmv8@vmv-valve.com](mailto:vmv8@vmv-valve.com)



[www.vmvvalve.com](http://www.vmvvalve.com)



Scan More Wonderful